

Dobo Hall Renovation - Package A

SCO PROJECT NO. 18-19798-01A

UNC Wilmington

4978 CAHILL DR, WILMINGTON, NC 28403

[illegible]

ELEVATOR PLAN AND DETAILS

A6.1.1

- A. REMOVE EXISTING HYDRAULIC ELEVATOR AND ALL ASSOCIATED COMPONENTS. FILL AND CAP EXISTING PISTON HOLE.
- B. EXTEND SHAFT HEIGHT WITH RATED CONSTRUCTION TO MATCH EXISTING
- C. REFER TO ELECTRICAL AND PLUMBING DRAWINGS FOR ADDITIONAL INFORMATION
- D. MODIFY SHAFT OPENINGS ARE DOORS TO ACCOMMODATE NEW WORK. MAINTAIN EXISTING SHAFT RATING REQUIREMENTS.
- E. FIELD VERIFY ALL EXISTING CONDITIONS.
- F. VERIFY REQUIREMENTS FOR INSTALLATION OF NEW DOOR SILLS

REPRESENTED BY

APPLIES TO DRAWINGS A

- 1 EXISTING SHAFT
- 2 PIT LADDER
- 3 EXISTING CONCRETE SILL TO REMAIN
- 4 ELEVATOR DOOR
- 5 16 GA SLOPED STAINLESS STEEL HOOD
- 6 CMU BOND BEAM
- 7 CMU INFILL
- 8 3"x3 WIDE BY 1/4" BENT STEEL PLATE; ANCHOR INTO PIT FLOOR
- 9 3/4" DIAMETER KNURLED STEEL RUNG; PLUG WELD TO STRINGERS
- 10 2 1/2" x 3/8" STEEL FLAT BAR STRINGERS
- 11 8 1/4" x 3" x 3/4" BENT STEEL PLATE; WELD TO STRINGER, BOLT TO WALL WITH 3/8" EXPANSION ANCHOR
- 12 HOIST BEAM, BY CM
- 13 1-HOUR RATED CONCRETE SHAFT CAP

