

GENERAL NOTES

- A. UNLESS INDICATED OTHERWISE, ALL COUNTERTOPS:
 - * 3/4" AFF OR 3/4" TO TOP OF RIM AT DROP-IN SINKS AND LAVATORIES WHERE OCCURS
 - * 2" DEEP
 - * BLACK EPOXY RESIN, 1" THICK
 - * BACKSPASHES: 4" HIGH AT PERIMETER AND AS NOTED
- B. UNLESS INDICATED OTHERWISE, ALL BASE CABINET(S):
 - * 22" DEEP NOMINAL
 - * TOE KICKS: 4" HIGH AND 3" DEEP
- C. UNLESS INDICATED OTHERWISE, ALL WALL CABINET(S):
 - * 11" DEEP NOMINAL
 - * 2-6" HIGH
 - * TOP AT 7'-0" AFF
- D. PROVIDE SOLID BLOCKING FOR ALL WALL MOUNTED ITEMS
- E. INSTALL RUBBER BASE ON THE BASE OF ALL CASEWORK
- F. BUILT-IN EQUIPMENT, SIZE OPENING (HEIGHT, WIDTH AND DEPTH) AND ROUGH-IN REQUIREMENTS AS REQUIRED BASED ON APPROVED MANUFACTURER SUBMITTED
- G. ALL SHELVES: ADJUSTABLE UNLESS INDICATED OTHERWISE.
- H. PROVIDE FINISH END PANELS AT ALL EXPOSED CASEWORK ENDS.
- I. LOCKS: AS INDICATED.
- J. MOUNT ALL WHITE BOARDS AND CHALK BOARDS AT 4'-0" AFF, UNO
- K. TALL STORAGE CABINETS SHALL BE SECURED TO THE WALL TO PREVENT TIPPING
- L. ALL LAB EQUIPMENT IS OFCI
- M. CM SHALL COORDINATE WITH OWNER FOR LOCATIONS OF OFCI PROJECTORS
- N. REFER TO SINK SCHEDULE FOR IDENTIFICATION OF FIXTURES AND ACCESSORIES

SCIENCE CASEWORK KEYNOTES

REPRESENTED BY n

PLIES TO DRAWINGS A7.4.1

- 1 RUBBER BASE
- 2 KNEE SPACE
- 3 BACK PANEL
- 4 END PANEL
- 5 SLIDING GLASS DOORS
- 6 FILLER PANEL
- 7 LOCK
- 8 FUME HOOD SHROUD, EXTEND TO CEILING
- 9 UNIVERSAL; SEE DETAIL n/A7.4.X
- 10 WALL SHELVING; SEE DETAIL n/A7.4.X
- 11 DRYING RACK; SEE DETAIL n/A7.4.X
- 12 ADJUSTABLE REAGENT SHELVING
- 13 REAGENT SHELVING; SEE DETAIL n/A7.4.X
- 14 ELECTRICAL RACEWAY

